



Verplaatsbare ontvochtigers - *Deshumidificateurs déplaçables* - Portable dehumidifiers



TYPE		T-20	T-40	TE-40	T-90	T-120
Voeding - <i>Alimentation</i> - Power Supply		220-240V/1/50Hz+T/E				
Max. m3 lokaal / local / room	m3	300	500	500	1.200	1.500
Verbruik - <i>Consommation</i> - Power Consumption	W	300	740	740	1.500	1.400
Ontvochtiging - <i>Deshumidification</i> - Moisture Removal						
- enkel ontvochtiging / <i>deshumidification seule</i> / dehumidifier only DIN 3167	L/24h.	20	40	40	90	120
- ontvochtiging + electr. verwarming / <i>deshumidification + chauffage électr.</i> / dehumidifier + electr. heater ⇒ enkel/seulement/only TE40	W	-	-	• 2.000	-	-
Werkingslimieten - <i>Limites de fonctionnement</i> - Working range	°C	0 ⇒ +35	0 ⇒ +35	0 ⇒ +35	0 ⇒ +35	0 ⇒ +35
bereik R.V. / <i>plage H.R.</i> / range R.H.	%	30 - 95 %	30 - 95 %	30 - 95 %	30 - 95 %	30 - 95 %
Luchtdebiet - <i>Débit d'air</i> - Air Flow	m3/h.	140	500	500	1.100	1.500
Ventilatiesnelheden - <i>Vitesses de Ventilation</i> - Fan Speed		1	1	1	1	1
Opvangbak condenswater - <i>Réceptier condensats</i> - Recipient cond. water	l	8	10	10	-	-
Afmetingen - <i>Dimensions</i> - Dimensions	mm	320x540x500	385x635x540	385x635x540	580x620x830	580x620x1.040
Gewicht - <i>Poids</i> - Weight	kg.	27	37	37	58	60
Koelmiddel - <i>Frigorigène</i> - Refrigerant		R407c				
Humidistaat - <i>Humidistat</i> - Humidistat		•	•	•	•	•
Hete-gasontdooiing - <i>Dégivrage à gaz chaud</i> - Hot gas de-icing		Electronisch / <i>Electronique</i> / Electronic				